

DUPLICATION CONTROLLING METHOD, DUPLICATION CONTROLLING
APPARATUS, RECORDING MEDIUM, AND DUPLICATION CONTROLLING
PROGRAM EMBODIED ON COMPUTER-READABLE MEDIUM

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to an electronic watermark embedding method and the like for embedding an electronic watermark to control the duplication of digital information contents.

2. Description of the Prior Art

Nowadays, digital television broadcast has been realized, so that the delivery of an image through an image digital signal is widely being performed. Moreover, there is being spread also a video recorder for recording an image as digital data onto an optical disc and a magnetic tape. If an image can be recorded as the digital data, it is possible to duplicate an image without deteriorating the quality of the image. Accordingly, from the viewpoint of copyright, it is necessary to limit the duplication of the image.

For example, European Patent Application EP1006722A2 (corresponding to Japanese Patent Application Laid-open No. 2000-173175) discloses a watermark (electronic watermark) technique as one of techniques to limit the duplication of the image by embedding information regarding the duplication limit in the digital image. The watermark is embedded so as to be hidden in the image. Accordingly, the watermark embedded in the image hardly lowers the image quality. Moreover, a person who has received the image having the watermark embedded probably cannot recognize that the watermark is present in the image, and

accordingly, it becomes very difficult to remove the watermark from the image.

The aforementioned EP1006722A2 discloses a system using a watermark indicating the prohibition of the duplication and a watermark indicating the allowance of one-generation duplication. Such a system can control the number of times that the duplication is performed, and accordingly, the system does not cause a copyright problem. Further, a person who receives television broadcast can watch a delivered image and without being restricted to a broadcast time.

In this system, when a digital image is supplied to a video recorder, the video recorder checks whether the image has a watermark. If one is present and it indicates to prohibit the duplication, the video recorder does not record the image. Moreover, when no watermark is present or a watermark is present but it indicates the allowance of one-generation duplication, the video recorder decides that the image is allowed to be duplicated and records the image onto an optical disc.

When an image is broadcast from a broadcast station, normally, a plurality of image contents are continuously broadcast. Accordingly, a variety of image contents, each having different image duplication control information, i.e., duplication prohibition, one-generation duplication allowance, duplication allowance, are successively broadcast. For example, the image contents having duplication control information indicating the duplication prohibition may be followed by the image contents of having duplication control information indicating the duplication allowance.

However, check to determine whether a watermark is present and detection of the watermark type switching from one to another require

a predetermined period of time (for example, a predetermined time not greater than 10 seconds). Therefore, the image contents switching may not be detected rapidly enough and at a head portion of the subsequent image contents, control information different from an actual one may be recognized.

For example, in a reception apparatus and a reproduction apparatus, there is caused a trouble of mismatching between control information based on a watermark and actual control information in a sector. This disturbs, for example, control of a micro vision signal as copy (duplication) control information to be added to an analog video signal. Moreover, a recording apparatus also has a problem. For example, even after the image contents are switched from those having control information of the duplication prohibition to those having control information of the duplication allowance, a head portion of the subsequent image contents is recognized as in the duplication prohibition and cannot be recorded. Moreover, even if the contents having control information of one-generation duplication allowance are switched to contents having control information of duplication allowance, a watermark of a duplicated state may be embedded to a head portion of the subsequent contents, and then the contents are scrambled. On the contrary, there is a trouble that a head portion of the contents whose duplication is prohibited is recorded.

SUMMARY OF THE INVENTION

It is therefore an object of the present invention to provide a duplication controlling method that can solve the problems caused by a detection delay of control information.

A first aspect of the present invention is directed to a

duplication controlling method for controlling duplication by embedding an electronic watermark indicating duplication-related control information into contents comprising digital information, wherein the electronic watermark includes change position information indicating a change position of the contents of the control information.

According to this duplication controlling method, it is possible to recognize a control information change position in advance by reading the watermark. This makes it possible to rapidly keep up with a control information change caused when the contents are switched from one to another for example.

It should be noted that in this Specification, the "change position of the contents of the control information" is a concept including an end of the control information, a start of the control information, and a switching position.

The change position information may indicate an end position of the contents having the electronic watermark.

In this case, the end position of the contents can be recognized in advance by reading the electronic watermark, which makes it possible to rapidly keep up with the control information change at the end of the contents.

The change position information may indicate a position where the contents of the control information indicated by the electronic watermark containing this change position information change to the subsequent contents.

In this case, the position where the control information contents are changed from one to another can be recognized in advance by reading the electronic watermark. Therefore, it is possible to rapidly keep up with

the control information switching.

The electronic watermark may contain contents information indicating the contents of the control information which is started from the change position.

5 In this case, an appropriate processing or operation can be assured in accordance with the contents of the control information which is started from the change position.

A plurality of change positions contained in the electronic watermark may be recorded as a table.

In this case, by reading the table once, it is possible to recognize all the change positions contained in the table. Accordingly, even if the contents are switched to other contents before their end, a necessary processing and operation can promptly be accomplished for the new contents.

15 The table may contain contents information indicating the contents of the control information which are started from a plurality of the change positions.

In this case, in accordance with the control information contents which are started at the change positions, it is possible to assure an appropriate processing and operation.

20 A second aspect of the present invention is directed to a duplication controlling apparatus for embedding an electronic watermark indicating control information regarding duplication into the contents comprising digital information. The apparatus is provided with: an
25 embedding device (201) for embedding the electronic watermark into the contents, wherein the electronic watermark contains change position information indicating a change position where the contents of the control

information are changed.

In this duplication controlling apparatus, because a control information contents change can be recognized in advance, it is possible to rapidly keep up with the control information change caused when the contents are switched from one to another.

The change position information may indicate an end position of the contents having the electronic watermark.

In this case, the end position of the contents can be recognized in advance by reading the electronic watermark, which makes it possible to rapidly keep up with the control information change at the end of the contents.

The change position information may indicate a position where the contents of the control information indicated by the electronic watermark containing this change position information change to the subsequent contents.

In this case, by reading the electronic watermark, it is possible to recognize in advance, the position where the control information contents are changed from one to another. Thus, it is possible to rapidly keep up with the control information switching.

The electronic watermark may contain contents information indicating the contents of the control information which is started from the change position.

In this case, an appropriate processing or operation can be assured in accordance with the contents of the control information which is started from the change position.

A plurality of change positions contained in the electronic watermark may be recorded as a table.

In this case, it is possible to recognize all the change positions contained in the table by reading the table. Accordingly, even if the contents are switched to other contents before their end, a necessary processing and operation can promptly be accomplished for the new contents.

The table may contain contents information indicating the contents of the control information which is started from a plurality of change positions.

In this case, according to the control information contents which are started from the change positions, it is possible to assure an appropriate processing and operation.

It may be possible to provide an delivery device (210, etc.) for delivering the contents having the electronic watermark embedded by the embedding device (201).

In this case, it is possible to appropriately keep up with a control information change of the contents delivered by the delivery device.

A third aspect of the present invention is directed to a recording medium (DK) having an electronic watermark indicating control information regarding the duplication of contents comprising digital information, wherein the electronic watermark includes change position information indicating a change position of the contents of the control information.

In this duplication controlling apparatus, because a control information contents change can be recognized in advance, it is possible to rapidly keep up with the control information change caused when the contents are switched.

The change position information may indicate an end position of

the contents having the electronic watermark.

5 In this case, the end position of the contents can be recognized in advance by reading the electronic watermark, which makes it possible to rapidly keep up with the control information change at the end of contents.

The change position information may indicate a position where the contents of the control information indicated by the electronic watermark containing this change position information changes to the subsequent contents.

In this case, the position where the control information contents are changed from one to another can be recognized in advance by reading the electronic watermark. Thus, it is possible to rapidly keep up with the control information switching.

15 The electronic watermark may contain contents information indicating the contents of the control information which is started from the change position.

In this case, an appropriate processing or operation can be assured in accordance with the contents of the control information which is started from the change position.

20 A plurality of change positions contained in the electronic watermark may be recorded as a table.

In this case, it is possible to recognize all the change positions contained in the table by reading the table. Accordingly, even if the contents are switched to other contents before their end, a necessary
25 processing and operation can promptly be accomplished for the new contents.

The table may contain contents information indicating the

contents of the control information which is started from a plurality of change positions.

In this case, in accordance with the control information contents which are started from the change positions, it is possible to assure an appropriate processing and operation.

A fourth aspect of the present invention is directed to a duplication controlling apparatus for performing control in accordance with duplication-related control information embedded in contents comprising digital information. The apparatus is provided with: an electronic watermark read device (107) for reading an electronic watermark; a change position detection device (104) for detecting a change position of the control information; and a control device (115) for modifying the processing of the duplication controlling apparatus when the change position is detected by the change position detection device (104), wherein the electronic watermark contains change position information indicating a change position of the contents of the control information.

According to this duplication controlling apparatus, it is possible to recognize the change position of the contents of the control information in advance when the electronic watermark is read by the electronic watermark read device. Accordingly, when a change position, for example, a switching position of the contents is detected, the processing can rapidly be switched to keep up with the control information change.

The change position information may indicate an end position of the contents having the electronic watermark.

In this case, the end position of the contents can be recognized in advance by reading the electronic watermark, which makes it possible

to rapidly keep up with the control information change at the end of the contents.

The change position information may indicate a position where the contents of the control information indicated by the electronic watermark containing this change position information change to the subsequent contents.

In this case, the position where the control information contents are changed from one to another can be recognized in advance by reading the electronic watermark. Thus, it is possible to rapidly keep up with the control information switching.

The change position information contained in the electronic watermark may be recorded as a table indicating a plurality of the change positions.

In this case, it is possible to recognize all the change positions contained in the table by reading the table. Accordingly, even if the contents are switched to other contents before their end, a necessary processing and operation can be accomplished for the new contents.

The table may contain contents information indicating the contents of the control information which is started from a plurality of the change positions.

In this case, in accordance with the control information contents which are started from the change positions, it is possible to assure an appropriate processing and operation.

The electronic watermark may contain contents information indicating the contents of the control information which is started from the change position, and the control device (115) may modify the processing in accordance with the contents information contained in the

electronic watermark.

In this case, in accordance with the contents of the control information which is started from the change position, an appropriate processing and operation can be performed.

5 An reproduction device (112, etc.) for reproducing the contents may be provided, and the reproduction device (112, etc.) may be controlled by the control device (115).

In this case, a change position of the contents of the control information can be recognized in advance by reading the electronic watermark with the electronic watermark read device, and accordingly, the operation of the reproduction device (112, etc.) can be switched upon detection of the contents switch position, which makes it possible to rapidly keep up with the control information.

15 An recording device (152, 155, 156, etc.) for recording the contents may be provided and the recording device (152, 155, 156, etc.) may be controlled by the control device (115).

20 In this case, a control information contents change position can be recognized in advance by reading an electronic watermark with the electronic watermark read device, and accordingly, it is possible to switch the operation of the recording device (152, 155, 156, etc.) upon detection of, for example, the contents switch position, thereby enabling to rapidly keep up with the control information change.

25 An reception device for receiving the contents may be provided, and the reception device (309, etc.) may be controlled by the control device (311).

In this case, a control information contents change position can be recognized in advance by reading the electronic watermark with the

electronic watermark read device, and accordingly, the operation of the reception means (309, etc.) can be switched upon detection of a change position such as a contents switch position by the change position detection device, thereby enabling to rapidly keep up with the control information change.

The present invention also provides a program for causing a computer to execute an embedding processing of an electronic watermark indicating duplication-related control information into contents comprising digital information. The program defines a procedure for inserting change position information indicating a control contents change position into the electronic watermark and a procedure for embedding the watermark into the contents.

The change position information may indicate an end position of the contents having the electronic watermark.

In this case, the end position of the contents can be recognized in advance by reading the electronic watermark, which makes it possible to rapidly keep up with the control information change at the end of the contents.

The change position information may indicate a position of switching from the contents of the control information indicated by the electronic watermark containing the change position information, to the subsequent contents.

In this case, the position where the control information contents are changed from one to another can be recognized in advance by reading the electronic watermark. Hence, it is possible to rapidly keep up with the control information switching.

The electronic watermark may contain contents information

indicating the contents of the control information which is started from the change position.

In this case, an appropriate processing or operation can be assured in accordance with the contents of the control information which is started from the change position.

The change position information contained in the electronic watermark may be recorded as a table indicating a plurality of the change positions.

In this case, by reading the table, it is possible to recognize all the change positions contained in the table. Accordingly, even if the contents are switched before its end to other contents, a necessary processing and operation can promptly be assured for new contents.

The table may contain contents information indicating the contents of the control information which is started from the plurality of change positions.

In this case, in accordance with the control information contents which are started from the change positions, it is possible to assure an appropriate processing and operation.

It should be noted that reference symbols used in attached drawings are attached to components of the present invention but the present invention is not to be limited to the embodiments in the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram showing a data layout of an optical disc to which a duplication controlling method according to the present invention is applied;

FIG. 2 is a diagram showing the contents of a watermark to be

embedded;

FIG. 3 is a block diagram showing configuration of an information recording/reproducing apparatus to/from an optical disc (DVD) using the duplication controlling method of the present invention;

FIG. 4 is a flowchart showing reproduction procedure in the information recording/reproducing apparatus;

FIG. 5 is a flowchart showing recording procedure in the information recording/reproducing apparatus;

FIG. 6 is a diagram showing an example of a watermark to be embedded into particular contents according to a second embodiment of the present invention;

FIG. 7 is a flowchart showing a reproduction procedure performed by the information recording/reproducing apparatus for reproducing a package medium having a table;

FIG. 8 is a flowchart showing a recording procedure performed by the information recording/reproducing apparatus for reproducing a package medium having a table;

FIG. 9 is a block diagram showing a configuration example of a transmission apparatus of a broadcast station; and

FIG. 10 is a block diagram showing a configuration example of a reception apparatus for receiving contents having an embedded watermark.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[First Embodiment]

Description will now be directed to a duplication controlling method according to a first embodiment of the present invention with

reference to FIGS. 1 to 5. It should be noted that in this embodiment, image contents are used as contents comprising digital information for example, but the present invention can be applied all the contents comprising digital information such as music.

FIG. 1 shows a data layout of an optical disc to which a duplication controlling method according to the present invention is applied.

As shown in FIG. 1, an optical disc DK has user data area and a lead-out area. In the user data area, video/audio information and navigation information related to video/audio information are alternately recorded. Moreover, at a head of the user data area, there is provided an area for recording a file system indicating hierarchical structure of the navigation information. Furthermore, a lead-in area is provided immediately before the user data area for recording disc information.

In each of the video/audio information areas, watermarks 1a and 2a are recorded together with video data as the data of contents 1 and contents 2. The watermarks indicate duplication controlling information (control information) for that video data. The watermarks 1a and 2a are repeatedly embedded in the video data.

In the example of FIG. 1, the contents 1 having control information of a duplication prohibition are followed by the contents 2 having control information of duplication allowance. The watermark 1a embedded in the contents 1 indicates control information (duplication allowed) of the contents 1, and the watermark 2a embedded in the contents 2 indicates control information (duplication prohibited) of the contents 2.

FIG. 2 shows a format of information embedded as a watermark.

In this example, the information indicated by the watermark is 16-byte data. One byte is embedded in one frame and 16 frames constitute an information item. These information items are embedded as watermarks in all the frames in the contents. As shown in FIG. 2, in this example, the watermark uses 1 byte for header information and control information, 2 bytes as information indicating an end position of current contents (during reproduction, reception, or recording), 1 byte for indicating control information of the subsequent contents, 3 bytes for copyright information, and remaining bytes for a reserved region and an error correction code.

Thus, in the first embodiment, the end position of the current contents and control information of the subsequent contents are recorded as a watermark. Accordingly, during reproduction, reception, or recording of the contents, it is possible to recognize in advance the timing for switching to the subsequent contents and the control information of the subsequent contents. That is, simultaneously with switching to the subsequent contents, it is possible to assure a correct operation according to the control information of the subsequent contents.

It should be noted that the contents end position can be defined by an address in the case of a package medium for example, but the present invention can be applied to other than the package medium. For example, in the case of broadcast medium, the contents end the position can be defined by a time stamp.

FIG. 3 is a block diagram showing configuration of an information recording/reproducing apparatus corresponding to the duplication controlling method of the present invention.

The information recording/reproducing apparatus 100, as a reproduction system, is provided with: a drive device 101 for an optical

disc DK; an optical head 102 for recording/reproducing information; a head amplifier 103 for amplifying an output signal of the optical head 102; a DVD demodulator 104 for performing demodulation, deinterleaving, descrambling, error correction, sector ID detection according to a DVD format; an RAM 105 for storing upon occasion, necessary data for DVD signal demodulation; a demultiplexer 106 for receiving an output signal from the DVD signal demodulator 105; a watermark detection block 107 which receives an output signal from the demultiplexer 106 and performs MPEG decoding of a video signal and an audio signal and which detects a video watermark and an audio watermark; an RAM 111 for storing the watermark detected; a signal overlap block 112 for overlapping a micro vision signal of CGMS-A type on the analog video output signal from an MPEG video recorder 107; a servo processing device 114 for controlling optical head focusing, tracking, and rotation speed of the optical disc DK; a CPU 115 for controlling the respective components of the information recording/reproducing apparatus 100; and an RAM 116 for storing upon occasion, data necessary for control by the CPU 115.

Moreover, the information recording/reproducing apparatus 100, as a recording system, is provided with: an interface (1394 interface) 151 for receiving a digital video signal; a detection/update device 152 for detecting/updating a video watermark in a video output signal from the interface 151; a detection/update device 153 for detecting/updating an audio watermark in an audio output signal from the interface 151; an RAM 154 for storing watermark detected; a multiplexer 155 for multiplexing the video output signal and the audio output signal from the detection/update devices 152 and 153; a DVD signal coding device 156 for performing a code processing based on the DVD format; and an optical

demodulator 157 for modulating an output signal from the DVD coding device 156 and outputting the demodulated signal to the optical head 102.

FIG. 4 is a flowchart showing an example of a reproduction procedure in the information recording/reproducing apparatus 100.

5 In FIG. 4, in step S1 a sector ID is detected and loaded. In step S2, according to the sector ID detection result in step S1, it is determined whether an end address of the contents which are being reproduced has been detected or not. If the result of the determination is affirmative, then the processing goes to step S3, and if the result of the determination is negative, then the processing goes to step S4. In step 3, an end flag is set to indicate that the contents end address has been detected, and the processing goes to step 5.

15 In step 5 it is determined whether the data is encrypted or not. If the result of the determination is affirmative, the processing goes to step S6 where decryption is performed, and the processing goes to step S7. If in step S5 it is determined that the data is not encrypted, then the processing directly goes to step S7.

20 In step S7, data is read, and in step S8, it is determined whether all the necessary data (data for one sector) have been read out. If the result of the determination is affirmative, the processing goes to step S9. If the result of the determination is negative, then the processing goes back to step S1.

25 In step S9 MPEG decoding is performed and in step S10 a watermark is detected. Next, in step S10 it is determined whether any watermark has been detected (or being detected) in step S10. If the result of the determination is affirmative, the processing goes to step S12. If the result of the determination is negative, then the processing directly goes to

step S25.

In step S12 it is determined whether a watermark has been detected. If the result of the determination is affirmative, then the processing goes to step S13. If the result of the determination is negative, then the processing goes to step S14. In step S13, the detected control information is loaded on a register for watermarks, and the processing goes to step S14.

Next, in step S14 it is determined whether a head address of the contents being reproduced is detected according to the sector ID detection result in step S1. If the result of the determination is affirmative, the processing goes to step S15, and if the result of the determination is negative, then the processing goes to step S16. In step S15, the contents of contents control information stored in a memory in step S23 (which will be detailed later) are loaded in the WM (watermark) register and the processing goes to step S16. It should be noted that various processes in this apparatus are performed according to the control contents loaded in step S15.

In step S16 it is determined whether a watermark is being detected. If the result of the determination is affirmative, the processing goes to step S17 and if the result of the determination is negative, then the processing goes to step S18. In step S17, control information in the sector ID is set in the signal overlap block 112 (FIG. 3) and the processing goes to step S20. Accordingly, during a period of time from a reproduction start to a watermark detection, the signal overlap block 112 is not set and the analog video signal does not enter the duplication allowance.

In step 18 it is determined whether the control information contents stored in the WM register in step S13 or step S15 coincides with

the sector ID control information of the sector which is being reproduced and has been read out. If the result of the determination is affirmative, the processing goes to step S19 and if the result of the determination is negative, then the processing goes to step S25. In step S25, it is assumed
5 that the control information in the ID might have been altered and a predetermined initialization process is executed, thereby terminating the processing shown in FIG. 4.

In step S19, the control information stored in the WM register is loaded in the signal overlap block 112. Next, in step S20 the end position of the contents which are being reproduced and the contents of the control information of the subsequent contents are read from the watermark. Next, in step S21 it is determined whether the end flag (step S3) has been set. If the result of the determination is affirmative, the processing goes to step S22 and if the result of the determination is negative, then the
15 processing goes to step S24.

In step S22, the contents of the control information in the WM register is reset (cancelled out of a storage), and in a subsequent step S23 the contents of the control information of the subsequent contents which have been read out in step S20 is loaded in a memory.

20 In step S24, the end flag is reset.

Next, in step S25 it is determined whether reproduction is complete. If the result of the determination is affirmative, the processing shown in FIG. 4 is terminated and if the result of the determination is negative, then the processing goes back to step S1.

25 Thus, in the processing of FIG. 4, an end address of the contents which are being reproduced and control information of the subsequent contents are read out (step S20). Upon detection of an end

flag which has been set by the end address of the contents (step S21: Yes), the WM register is cleared (step S22) and control information of the subsequent contents is loaded in the memory (step S23). Upon detection of a head address of the subsequent contents (step S14: Yes), the control information of the contents which has been loaded in the memory is loaded in the WM register (step S15), thereby controlling the signal overlap block 112 (step S19). Accordingly, without being affected from a delayed detection of a watermark and it is possible to add a correct micro vision signal corresponding to the contents, to an analog video signal, as the contents change from one to another.

FIG. 5 is a flowchart showing an example of recording procedure in the information recording/reproducing apparatus 100.

In FIG. 5, in step S101 a header ID is detected and loaded. In step S102, according to the header ID detection result in step S101, it is determined whether an end address of the contents which are being recorded as digital video data has been detected. If the result of the determination is affirmative, the processing goes to step S103. If the result of the determination is negative, the processing goes to step S104. In step S103 an end flag is set to indicate that the contents end address has been detected, and the processing goes to step S105.

In step 105 it is determined whether the data is encrypted. If the result of the determination is affirmative, the processing goes to step S106, where the data is decrypted, and the processing goes to step S107. If in step S105 it is determined that the data is not encrypted, the processing goes to step S107.

In step 107, the data is read out and in step S108 it is determined whether all the necessary data (data for one sector) have been

read out. If the result of the determination is affirmative, the processing goes to step S110. If the result of the determination is negative, the processing goes back to S101.

Subsequently, in step S110 a watermark is detected. It should be noted that in the case that the contents to be recorded have been subjected to MPEG data compression, MPEG decoding is executed prior to step S110. Next, in step S111 it is determined whether a watermark has been detected (including a state of being detected) in step S110. If the result of the determination is affirmative, the processing goes to step S112 and if the result of the determination is negative, then the processing goes to step S124.

In step S112 it is determined whether a watermark was able to be detected. If the result of the determination is affirmative, the processing goes to step S113 and if the result of the determination is negative, then the processing goes to step S114. In step S113, the detected control information is loaded in the WM register and the processing goes to step S114.

Next, according to the header ID detection result in step S101, in step S114 it is determined whether the contents head address has been detected. If the result of the determination is affirmative, the processing goes to S115 and if the result of the determination is negative, then the processing goes to step S116. In step S115, control information stored in a memory in step S128 (which will be detailed later) is loaded in the WM register and the processing goes to S116. It should be noted that various processes are executed in the present apparatus according to the control information loaded in step S115.

In step S116 it is determined whether a watermark is being

detected. If the result of the determination is affirmative, the processing goes to step S119, and if the result of the determination is negative, then the processing goes to step S117.

In step S117 it is determined whether the control information stored in the WM register in step S113 or S115 coincides with the control information of the sector which is being recorded. If the result of the determination is affirmative, the processing goes to step S119, and if the result of the determination is negative, then the processing goes to step S118. In step S118, a predetermined initialization is executed which is executed when an abnormal operation is detected, thereby terminating the processing shown in FIG. 5.

In step S119 it is determined whether the contents to be recorded are in the duplication allowance. If the result of the determination is affirmative, the processing goes to step S124, and if the result of the determination is negative, the processing goes to step S121. In step S121 it is determined whether the contents to be recorded are in the duplication prohibition or in the further duplication prohibition (one-generation duplication allowed but already recorded once). If the result of the determination is affirmative, the processing goes to step S122, and if the result of the determination is negative, then the processing goes to step S123. It should be noted that in step S123 the result of the determination becomes negative when current recording is a first generation recording of the contents in the one-generation duplication allowance. In step S122 warning display is performed and the processing goes to S125.

In step S123 a flag prohibiting further duplication is set and the processing goes to step S124.

It should be noted that when this flag is set, the aforementioned detection/update device 152, 153 (FIG. 3) update the watermark by embedding a second watermark into each of the input signals. The second watermark indicates that duplication (copying) has been performed once. Moreover, the DVD signal coding device 156 performs a predetermined encryption of the input signals.

In step S124, contents data is recorded and the processing goes to step S125.

Next, in step S125 the contents of the watermark, i.e., an end position of the contents which are being recorded and control information of the subsequent contents are read out. Next, in step S126 it is determined whether the end flag (step 103) has been set. If the determination is affirmative, the processing goes to step S127, and if the result of the determination is negative, the processing goes to step S130.

In step S127 the contents of the control information in the WM register are reset (cancelled out of a storage), and then in step S128 the contents of control information of the next contents which have been read out in step S125 is loaded in the memory. In step S129, the end flag is reset.

Next, in step S130 it is determined whether the recording is complete. If the result of the determination is affirmative, the processing shown in FIG. 5 is terminated. If the result of the determination is negative, then the processing goes back to step S101.

Thus, in the processing shown FIG. 5, by reading out an end address of the contents which are being recorded and control information of the subsequent contents (step S125) and detecting the end flag which has been set at the recorded contents end address (step S126: Yes), the

WM register is cleared (step S127) and control information of the subsequent contents is loaded in the memory (step 128). When a head address of the subsequent contents is detected (step S112: Yes), control information of the subsequent contents which have been stored in the memory is loaded in the WM register (step S113), enabling to recognize the control information (step S119, step S121). Accordingly, without being affected by a watermark detection delay, control information corresponding to the contents can immediately be recognized as the contents are switched from one to another.

[Embodiment 2]

While in the first embodiment, each of the contents watermarks contains an end position of the contents and control information of the subsequent contents, in the second embodiment, a particular contents watermark contains a change position of control information and control information contents are intensively recorded as a table.

FIG. 6 shows an example of information contained as a watermark embedded into particular contents according to the second embodiment.

In the example of FIG. 6, as a watermark, following information is recorded: a control information change position ("first change position" in FIG. 6) corresponding to switching from the current contents (first contents) to the subsequent contents (second contents) and control information before and after the change; a control information change position ("second change position" in FIG. 6) corresponding to switching from the second contents to the subsequent contents (third contents) and control information before and after the change position. It should be noted that FIG. 6 shows a table example when the table can be expressed

in 256 bytes. Control information of copyright and control information of the current contents (which is being reproduced, being received, or being recorded) are contained in each of the contents in the same way as the first embodiment.

5 In the case of a package medium, such a table includes control information change positions corresponding to switching positions of all the contents recorded in that medium and is embedded as a watermark with a high intensity into a position which is surely read in upon disc start (such as a title # and chapter # recorded in the disc, a menu screen for selecting a caption language, and a head portion of the first contents (title #1) to be reproduced). It should be noted that in addition to this table, control information for each of the contents is embedded so as to protect copyright.

15 Moreover, when delivering the contents by broadcast, the table contains control information change positions corresponding to switching positions of the contents of a predetermined range and control information before and after the changes, and the table is embedded as a watermark with a comparatively long cycle.

20 In the case of package medium, a control information change position can be defined by an address. Moreover, when delivering software by broadcast, the control information change position can be defined by a time stamp.

25 In this case, the second change position and subsequent change positions only need to indicate a relative time stamp from the time stamp where the watermark of the first change position is embedded.

FIG. 7 is a flowchart showing an example of operation procedure when reproducing a package medium having a table as shown in FIG. 6 by

the information recording/reproducing apparatus 100 (FIG. 3).

In step S201 of FIG. 7, a sector ID is detected and set.

In step S205, it is determined whether data is encrypted. If the result of the determination is affirmative, the processing goes to step S206, where decryption is executed and then the processing goes to step S207. If step S205 decides that the data is not encrypted, the processing goes to step S207.

In step S207, the data is read out and in step S208 it is determined whether all the necessary data (data of one sector) have been read out. If the result of the determination is affirmative, the processing goes to step S209, and if the result of the determination is negative, the processing goes back to step S201.

In step S209, MPEG decoding is executed and in step S210, a watermark is detected. Next, in step S211, it is determined whether a watermark has been detected (including a state that a watermark is being detected). If the result of the determination is affirmative, the processing goes to step S212, and if the result of the determination is negative, then the processing goes to step S224.

In step S212 it is determined whether a watermark has been detected. If the result of the determination is affirmative, the processing goes to step S213, and if the result of the determination is negative, then the processing goes to step S216. In step S213 it is determined whether the watermark detected is one shown in the table of FIG. 6. If the result of the determination is affirmative, the processing goes to step S214, and if the result of the determination is negative, then the processing goes to step S215. In step S214, currently reproduced control information and the table are read in and stored. Then, the processing goes to step S215,

where the currently reproduced control information is loaded in the WM register and the processing goes to step S216.

Next, according to the sector ID detection result in step S201, in step 216 it is determined whether an address at which the contents being reproduced are changed has been detected. If the result of the determination is affirmative, the processing goes to step S217, and if the result of the determination, then the processing goes to step S218. In step S217, from the table stored in step S214, control information of the next contents to be reproduced is loaded in the WM register and the processing goes to step 218. It should be noted that various processes in the present apparatus are performed according to the control information set in step S217.

In step S218 it is determined whether a watermark is being detected. If the result of the determination is affirmative, the processing goes to S219, and if the result of the determination is negative, then the processing goes to step S220. In step S219, the control information of the sector ID is set in the signal overlap block 112 (FIG. 3) and the processing goes to step S223. Accordingly, during a period of time from the reproduction start to the watermark detection, the signal overlap 112 is not set and the analog video signal does not enter the duplication allowance.

In step 220 it is determined whether the control information stored in the WM register in step S215 or step S217 coincides with the control information of the sector which has been read out and is being reproduced. If the result of the determination is affirmative, the processing goes to step S221, and if the result of the determination is negative, then the processing goes to step S222. In step S222, assuming

that the ID control information has been altered, a predetermined initialization is executed, thereby terminating the processing of FIG. 7.

In step S219, the control information stored in the WM register is set in the signal overlap block 112.

Next, in step S223 it is determined whether the reproduction is complete. If the result of the determination is affirmative, the processing of FIG. 7 is terminated, and if the result of the determination is negative, the processing goes back to step S201.

Thus, in the processing shown in FIG. 7, the contents of the table shown in FIG. 6 are stored (step S214) and when a contents change address is detected (step S216: Yes), next control information to be reproduced is fetched from the stored table and set in the WM register (step S217) so as to control the signal overlap block 112 (step S221). Accordingly, without being affected by a watermark detection delay, a correct macro vision signal corresponding to the current contents which is switched to the subsequent contents can be added to the analog video signal. Furthermore, since the table is stored, even if it transfers to the reproduction by skipping some contents, the control information of the contents is recognized simultaneously with the reproduction of that contents, and a correct micro vision signal can immediately be added to the analog video signal.

FIG. 8 is a flowchart showing an example of operation procedure when recording a package medium having the table of FIG. 6 by the information recording/reproducing apparatus 100 (FIG. 3).

In step S301 of FIG. 8, a header ID is detected and set.

In step S305 it is determined whether data is encrypted. If the result of the determination is affirmative, the processing goes to step S306

where decryption is executed and the processing goes to step S307. If in step S305 it is determined that data is not encrypted, the processing goes to step S307.

In step S307, data is read and then in step S308 it is determined whether all the necessary data (data of one sector) have been read out. If the result of the determination is affirmative, the processing goes to step S10, and if the result of the determination is negative, the processing goes back to step S301.

Subsequently, in step S310, a watermark detection is executed. It should be noted that when the contents to be recorded have been subjected to MPEG data compression, MPEG decoding is executed prior to step S310. Next, in step S311 it is determined whether a watermark has been detected (including a state that a watermark is being detected). If the result of the determination is affirmative, the processing goes to step S312, and if the result of the determination is negative, then the processing goes to step S324.

In step S312 it is determined whether a watermark was able to be detected. If the result of the determination is affirmative, the processing goes to step S313, and if the result of the determination is negative, the processing goes to step S316. In step S313 it is determined whether the watermark detected is one shown in the table of FIG. 6. If the result of the determination is affirmative, the processing goes to step S314, and if the result of the determination is negative, then the processing goes to step S315. In step S314, together with the control information which is being recorded, the table of FIG. 6 is read in and stored, and the processing goes to step S315. In step S315, the control information which is being recorded is loaded in the WM register and the processing goes to

step S316.

Next, according to the header ID detection result in step S301, in step S316 it is determined whether a head address of the contents which are being recorded has been detected. If the result of the determination is affirmative, the processing goes to step S317, and if the result of the determination, then the processing goes to step S318. In step S317, control information of the subsequent contents to be recorded is loaded in the WM register from the table stored in the preceding step S314, and the processing goes to S318. It should be noted that various processes in the present apparatus are performed according to the control information set in step S317.

In step S318 it is determined whether a watermark is being detected. If the result of the determination is affirmative, the processing goes to step S322, and if the result of the determination is negative, then the processing goes to step S320.

In step S320 it is determined whether the control information stored in the WM register in step S315 or step S317 coincides with the control information of the sector which is being recorded. If the result of the determination is affirmative, the processing goes to step S322, and if the result of the determination is negative, then the processing goes to step S321. In step S321, a predetermined initialization process is executed, assuming that the ID control information has been altered.

In step S322 it is determined whether the contents to be recorded are in the duplication allowance according to the ID control information when the watermark is being detected or according to the control information in the watermark register when the watermark has been detected. If the result of the determination is affirmative, the

processing goes to step S326, and if the result of the determination is negative, then the processing goes to step S323. In step S323 it is determined whether the contents to be recorded are in the duplication prohibition or further duplication prohibition (one-generation duplication is allowed but already recorded once) according to the control information like the determination in step S322. If the result of the determination is affirmative, the processing goes to step S324, and if the result of the determination is negative, the processing goes to step S325. It should be noted that the result of the determination in the step S325 is negative when a current recording is the first generation recording for the contents. In step S324, a warning message is displayed and control is passed to step S327.

In step S325 flag indicating that further duplication is prohibited is set and the processing goes to step S326.

It should be noted that when this flag is set, the aforementioned detection/update devices 152 and 153 (FIG. 3) embed into input signals a second watermark indicating that duplication (copying) has been performed once, so as to update the watermark. Moreover, the DVD signal coding device 156 executes a predetermined encryption process to the input signals.

In step S326, the contents data is recorded and the processing goes to step S327.

Next, in step S327 it is determined whether the recording is complete. If the result of the determination is affirmative, the processing of FIG. 8 is terminated, and if the result of the determination is negative, then the processing goes back to step S301.

Thus, in the processing shown in FIG. 8, the table of FIG. 6 is

stored (step S314) and upon detection of a contents change address (step S316: Yes), a next control information to be recorded is fetched from the stored table and loaded in the WM register (step S317) and the control information is checked (step S322, step S323). Accordingly, without being
5 affected by a watermark detection delay, correct control information corresponding to the change of the contents can be immediately obtained.

FIG. 9 is a block diagram showing a configuration example of a transmission apparatus of a broadcast station capable of embedding a watermark into the broadcast contents according to the duplication
10 controlling method of the present invention.

The transmission apparatus 200 shown in FIG. 9 is provide with: a plurality of watermark embedding blocks 201; a multiplexer 208 for embedding a header and multiplexing an output signal from the watermark embedding block 201; a modulation block for modulating an output signal from the multiplexer 208 and, if necessary, scrambling an image; and a transmitter 210 for amplifying and outputting an output
15 signal from the modulation block 209.

As shown in FIG. 9, the watermark embedding block 201 includes a video cassette recorder 202 for reproducing a video tape having
20 the recorded contents; a watermark embedding device 203 for embedding a watermark into an output signal (image signal) from the video cassette recorder; an encoder 204 for executing data compression of a video signal and an audio signal of the contents output from the video cassette recorder, using the MPEG method and the AC3 method, respectively; a
25 contents delimiting information generator 205 for outputting an end, a head, and a switching timing of the contents as well as the contents of the control information of the contents; and a contents control device 206 for

controlling the video cassette recorder 202 and the contents delimiting information generator 205.

In the watermark embedding block 201, a watermark is embedded by the watermark embedding device 203 into a video signal and an audio signal of the contents output from the video cassette recorder 202. The contents delimiting information generator 205 output to the watermark embedding device 203 a time stamp indicating a contents delimiting timing and information indicating the contents of control information. Thus, the time stamp indicating the contents delimiting timing and the watermark having the information indicating the contents of the control information are added to a video signal or an audio signal.

By using the transmission apparatus of FIG. 9, for example, it is possible to embed, into the contents, a watermark indicating the end of the contents and the contents of the control information of the subsequent contents as in the first embodiment, and to embed as a watermark a table containing a plurality of control information change positions and the contents of the control information, into particular contents as in the second embodiment before broadcasting a plurality of contents continuously or at a predetermined interval.

The processing in the transmission apparatus 200 can be executed by a computer (such as a contents control device) according to a readable software program. In this case, the contents delimiting information generator 205, which is controlled by the contents control device 206, can be served as an inserting device for inserting change position information indicating a change position of the contents of the control information into a watermark. The watermark embedding device 203, which is controlled by the contents control device 206, can be served

as an embedding device for embedding a watermark into the contents.

FIG. 10 is a block diagram showing a configuration example of a reception apparatus for receiving the contents having a watermark embedded according to the duplication controlling method of the present invention.

The reception apparatus shown in FIG. 10 is provided with: a demodulator 301 for demodulating a received signal which has been modulated by 4-phase modulation method; a descrambler 302 for removing a scramble from an output signal of the demodulator; an MPEG decoder 303 which is fed with an image signal from the descrambler 302; an AC3 decoder 304 fed with a voice signal from the descrambler 302; a header extracting block for extracting header information from an output signal of the descrambler 302; a watermark detection block 307 for detecting a watermark in the MPEG-decoded image signal; watermark detection block 308 for detecting a watermark in the AC3-decoded voice signal; a signal overlap block 309 for overlapping an output signal from the watermark detection block 307 with a macro vision signal of CGMS-A method; and a CPU 311 for controlling the respective blocks of the reception apparatus 300.

In this reception apparatus 300, it is possible to obtain a time stamp indicating a contents delimiting timing and information indicating the contents of control information by detecting a watermark embedded in a video signal and an audio signal of the contents, using the watermark detection device 307. This makes it possible to rapidly control the signal overlap block 309 according to the contents delimiting timing. As an actual processing, the procedures shown in FIG. 4, FIG. 5, FIG. 7 or FIG. 8 are performed to pre-detect a contents delimiting or control information

change timing, the contents of the control information switched from one to another, and the like. Thus, it is possible to detect the end of the contents and the contents of the control information of the subsequent contents as in the first embodiment and to read a table containing a plurality of control information change positions and the contents of control information, and the like.

It should be noted that the present invention is not limited to the aforementioned embodiments. For example, while in the example of FIG. 2, a watermark indicates an end position of the current contents as information of a control information contents change position, it is also possible to indicate a head position of the subsequent contents.

As has been described above, according to the present invention, an electronic watermark including change position information indicating a control information contents change position is embedded into contents comprising digital information. Accordingly, upon reproduction, recording, or reception, the electronic watermark can be read out so as to recognize a control information contents change position in advance. Consequently, it is possible to rapidly keep up with control information change occurring when the contents are switched from one to another.

The invention may be embodied in other specific forms without departing from the spirit or essential characteristics thereof. The present embodiments are therefore to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by the appended claims rather than by the foregoing description and all changes which come within the meaning and range of equivalency of the claims are therefore intended to be embraced therein.

The entire disclosure of Japanese Patent Application No. 2001-

64008 filed on March 7, 2001 including the specification, claims, drawings and summary is incorporated herein by reference in its entirety.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2